

- The Alphatech Alarm intercom unit is powered from telephone line only
- The unit includes microphone and speaker
- Programming is either remotely by phone (DTMF tones) or by PC (cable on USB port)
- Indication light (by connected LEDs) – yellow, indication of dialling the number, green, indication confirm of call
- One emergency pushbutton
- Special mode with autoblocking function (from moving of cabine door)
- The time of button activation is adjustable from 0,5 sec to 39 sec, standard 5sec.
- Inputs on the unit are galvanically connected with telephone line, inputs with note „Isol.“ are isolated and activation is possible by external voltage only
- Automatic control of functionality - Service call (automatic calling to preprogrammed numbers in set time period from 1 to 59 days)
- Possible to activate acoustic ticking to the conversation for a speech recognition
- Adjustable parameters of tone dialling, length of Flash and Pause
- Adjustable parametres of tones detector amd parametres of acoustical signalization
- Electronic loudness settings (without neccessity to open the unit)
- Possibility to program 6 numbers (16 digits – includes *,#,Pause,Flash) with a note if you need to use call confirmation or not. The numbers are progressively dialled
- Memory on two last dialled phone numbers
- Technical call with various states (e.g. a pushbutton is pressed pernamently, acoustic test)
- Automatic test of acoustic path (microphone and speaker). Switchtable by a parameter
- Automatic test of permanently activated button
- Posibility to set mute for service and technical calls

